



One (1) Reconditioned Westfalia Self-Cleaning centrifuge to include:

Max. Hydraulic Capacity: 90 GPM
Max. Process Capacity: Varies depending on process conditions
Viton o-rings used in product contact areas
Direct-drive design
Variable shoot design (partial or full shot)
Stainless steel rotating assembly
Powder-coated grey iron frame and silumin cover
20 HP Class 1., Div. 1 explosion-proof motor – 460/480 Volt, 3 phase, 60 cycle.
Heavy Phase (water) discharged by gravity
Light Phase (oil) discharged under pressure by means of a paring disk (centripetal pump)
One (1) set of regulating discs
One (1) set of necessary special tools
One (1) set of spare bowl o-rings
One (1) copy of the Operation / Spare party Manual
Feed pump not included. Customer required to supply their own feed pump.

New Control Panel to include:

*For use in non-hazardous duty area. Indoor use only.
20 HP Variable Frequency Drive (wall-mount installation). 460/480 Volt, 3-phase, 60 cycle input power required.
Time to operate bowl shoot/close water
Timer to operate 3-way feed and bypass valve
Completely wired and tested

New Feed Valve System to include:

3-way solenoid feed valve

New Operating Water System to include:

Shoot/Close electric air solenoid valve
Purge/Prime electric air solenoid valve

Warranty to include:

Six (6) month limited warrant (centrifuge).
One (1) year limited warranty (control system and motor).

Start Up Assistance offered:

Two (2) days of on-site start-up assistance included. Travel and living expenses are invoiced at cost.

PRICE: \$75,000
F.O.B. Florida
DELIVERY: 6-8 weeks
TERMS: 50% with Purchase Order and Signed Sales Contract
50% Prior to Shipment

Please Note: Customer is responsible for all sales taxes associated with purchase