



Ultra Vac Model: UV-5

Standard Features

- 300 GPH Process Flow Rate
- 5kW Heater w/ Programmable Temperature Controller
- Dry Seal Vacuum Pump w/ Oil Sump
- Electrical Controls, w/ "On" indicator, alarm lights and phase monitor
- 440V-3Ph-60Hz Power
- Adjustable Flow Control
- W32"xL40"xH60"
- 750 lbs
- Sample Ports
- Pressure Gauge
- Non-Re-settable Hour Meter
- 80CN Parker Filter Housing
- 4" Caster Wheels
- 25' Electrical Cord
- One Year Warranty
- Operational & Maintenance Manual w/ Spare Parts List

Safety Features

- High Temp Shutdown Circuit
- High Oil Level Shutdown
- High Condensate Tank Shutdown

Standard Options

- Fork Lift Pockets
- Heat Recovery System
- Inlet & Outlet Hoses
- 220V-3Ph-60Hz Power
- Feed Shutoff Valve
- Flow Meter
- Auto Condensate Drain

The UV-5 is a highly efficient, compact vacuum dehydration unit capable of removing water from most lubricating, EHC and hydraulic fluids down to 150 ppm. It is designed for 400 - 1,100 gallon systems. The UV-5 requires 440 volt, 3 phase power supply. Options and custom modifications are available.



INDUSTRIAL FLUID SYSTEMS

22200 Ryan Road
Warren, MI 48091

Phone: 800-343-8106

Fax: 586-754-8284

www.industrialfluidsystems.com