

5 1/4" DIA. TUBULAR SCREW CONVEYOR GENERAL ARRANGEMENT – TAG SC-408

SCALE: 1 1/2" = 1'-0"

NOTE:
THIS CONVEYOR IS INCLINED AT 30.00 DEGREES.
ALL SUPPORTS BY OTHERS

SECTION THRU HANGER POCKET
SCALE: 1 1/2" = 1'-0"



SECTION THRU CONVEYOR
SCALE: 1 1/2" = 1'-0"



INLET/DISCHARGE FLANGE DETAIL (10GA)
SCALE: 3" = 1'-0"

NOTES

1. 5 1/4" DIA TUBULAR SCREW CONVEYOR (NL537A SPEC. BASED ON THE FOLLOWING
   - OVERALL LENGTH - 17'-0" END PLATE TO END PLATE
   - INCLINE DEGREES - 30 DEG.
   - CAPACITY - 18 CFH
   - PRODUCT - SUBSOIL MATERIAL
   - PRODUCT DENSITY - 42 lb/cu ft
   - FINAL RPM - 62
2. PAINT SPECIFICATION
   - EXTERIOR PAINT SYSTEM - PRIMER ONLY
   - EQUIPMENT COLOR: N/A

   SAFETY SURFACES
   - PREPARATION SSPC-2
   - PRIMER: ONE CO COAT OF ALKYD PRIMER
   - FINISH: ONE CO COAT OF ALKYD QUICK AIR DRY ENAMEL
   - COLOR: SAFETY ORANGE - 549-N618
3. CONVEYOR TO BE SHOP ASSEMBLED AND TEST RUN PRIOR TO SHIPMENT
4. CONVEYOR TO BE MATCH MARKED AND TAGGED PRIOR TO SHIPMENT
5. EQUIPMENT TAG No.
   - SC-408

ITEM	PART NO.	DESCRIPTION	QTY
23	C990-31604W	5 1/4" DIA RH, 5 1/2" PITCH SECTIONAL SCREW X 17'-4-31/16" C/W 3/16"	1
		THK HRMS FLIGHTS INTERMITTENTLY WELDED TO 21' SCH 80 PIPE BUSHED	
		AND DRILLED FOR 1 1/2" DIA 2-BOLT SHAFT, C/W BARE PIPE	
22	36733W	6" SCH 40 STD.ID TUBULAR TROUGH WELDMENT X 17'-4" LG C/W 7"x9"	1
		HANGER BEARING POCKET AND CLOSE 7"x9" STUB DISCHARGE FITTER	
21	10K3332	CC112-16, 5 1/16" DIA, HARDENED COUPLING SHAFT,2 -HEX KEY	1
20		3/8" X 1" BOLT - 25 1/2" EFEC.	4
19		5/8" UNC X 2 3/4 GR5 HEX BOLT C/W NUT, LW & FW	4
18		3/8" UNC X 2 GR5 HEX BOLT C/W NUT, LW & FW	4
17		3/8" UNC X 1" WHEELOCK BOLT C/W NUT	2
16		STANDARD CAULKING FOR END FLANGE CONNECTIONS	1
15	10K5330	10GA TUBULAR TROUGH SUPPORT FOOT	2
14		1/2" UNC X 2" GR5 COUPLING BOLT C/W UNI-TORQUE NUT	6
13	20L300A	SOURCE TAG007 MOTOR MOUNT - K1706	1
12		2B1000K MSK DRIVEN SHEAVE C/W SDS 1 MSK BUSHINGS	1
11		2B1615DS MSK DRIVE SHEAVE C/W SDS 7/8 MSK BUSHINGS	1
10	10K6528RW	ENCLOSED V- BELT DRIVE GUARD	1
9		5HP, WILL WIRE TEFC NEMA PREM. EFF. ELEC. MOTOR	1
		3/60/460V, 1800 RPM FRAME 184T	
8		MODEL TA007A-15 DOUBLE SHAFT MOUNTED REDUCER UNIT MOUNTED AT 30DEG	1
		CW, RATED FOR CLASS II SERVICE AT 62 RPM OUTPUT SPEED WITH NA	
		1 1/2" DIA SHOCK SHAFT, AND QDT ADAPTOR KIT TO SUIT	
7		CC112, 2" DIA HRMS IRON HANGER END BEARING INSERT	1
6	10K6529	CW4210QE, 6" HANGER END FRAME STYLE 2DS FOR 1 1/2" DIA SHAFT	1
5	10K3527	10GA HRMS TUBULAR TROUGH BLANK TAIL END PLATE	1
4	10K6526	10GA HRMS, TUBULAR TROUGH DRIVE END PLATE FOR 1 1/2" DIA SHAFT	1
3			
2	36733W	10" SCH 40 SOLID TUBULAR TROUGH WELDMENT X 17'-0" LG C/W 7"x9"	1
		HANGER BEARING POCKET AND 7"x7" GR FLANGED INLET FITTER	
1	C990-31614W	5 1/4" DIA RH, 5 1/2" PITCH SECTIONAL SCREW X 17'-0" LG C/W 3/16"	1
		THK HRMS FLIGHTS INTERMITTENTLY WELDED TO 21' SCH 80 PIPE BUSHED	
		AND DRILLED ON BOTHE ENDS FOR 1 1/16" DIA 2-BOLT SHAFT, TAIL END	
		WELDED-IN 1 1/2" DIA HARDENED HANGER END SHAFT, AND BARE PIPE	

DATE	NO.	DESCRIPTION	BY
30 JAN 2023	6	CORRECTED MOTOR	KAK
26 JAN 2023	5	CORRECTED COUPLING SHAFT P/N	KAK
24 OCT 2022	4	RELEASED FOR CONSTRUCTION	V.K.
13 OCT 2022	3	UPDATED DISCHARGE FROM 90 DEG TO 0 DEG	V.K.
29 SEP 2022	2	INCREASED CONVEYOR LENGTH BY 3', ADDED HANGER POCKET, HANGER, COUPLING SHAFT, PIPE, INLET PIPE	V.K.
07 DEC 2022	1	ADDED TAG #, FLANGE SIZES	KAK

DATE: DESIGN: DR. V.K. TR. CH. DATE 1 DEC 2022

ARJAE DESIGN SOLUTIONS LTD, NISKU, AB

5 1/4" DIA. INCLINED TUBULAR SCREW CONVEYOR ASSY X 17'-0" LG

MATERIAL: AS NOTED

SCALE: NOTED

DWG NO. 4031778

Nordstrong Equipment Limited